

# oioenergy2

Vienna University of Technology

# Advanced biofuels by gasification -Status of R&D work in Güssing

Reinhard Rauch

Institute of Chemical Engineering **Working Group Future Energy Technology** Prof. Hermann Hofbauer



Scientific partners





Engineering (as example)




Operators (as example)







## The basic concept – "Green Chemistry"





### BioSNG demonstration plant



Gasifier

BioSNG PDU

**Technikum** 

**Fuelling Station** 



# Commercial FICFB gasifiers

Location	Electricity production	Fuel / electr. MW, MWel	Start up	Status
Güssing, AT	Gas engine	8.0 / 2.0	2002	Operational
Oberwart, AT	Gas engine / ORC	8.5 / 2.8	2008	Operational
Villach, AT	Gas engine	15 / 3.7	2010	Commissioning
Klagenfurt, AT	Gas engine	25 / 5.5	2011	planing
Ulm, DE	Gas engine / ORC	14 / 5	2011	Under construction
Göteborg, Sweden	BioSNG	32/20 (BioSNG)	2012	planing



# Gas Composition (after gas cleaning)

Main Components				
H <sub>2</sub>	%	35-45		
СО	%	22-25		
CH <sub>4</sub>	%	~10		
CO <sub>2</sub>	%	20-25		

Minor Components				
C <sub>2</sub> H <sub>4</sub>	%	2-3		
C <sub>2</sub> H <sub>6</sub>	%	~0.5		
C <sub>3</sub> H <sub>4</sub>	%	~0,4		
O <sub>2</sub>	%	< 0,1		
N <sub>2</sub>	%	1-3		
C <sub>6</sub> H <sub>6</sub>	g/m³	~8		
C <sub>7</sub> H <sub>8</sub>	g/m³	~0,5		
C <sub>10</sub> H <sub>8</sub>	g/m³	~2		
TARS	mg/m³	20-30		

Possible poisons				
H <sub>2</sub> S	mgS/Nm³	~200		
cos	mgS/Nm³	~5		
Mercaptans	mgS/Nm³	~30		
Thiophens	mgS/Nm³	~7		
HCI	ppm	~3		
NH3	ppm	500-1000		
HCN	ppm	~100		
Dust	mg/Nm³	< 20		

 $H_2$ :CO = from 1.7:1 to 2:1

PAUL SCHERRER INSTITUT



### BioSNG Demonstration Project

A 1 MW SNG Process Development Unit (PDU) is erected within the EU project BioSNG and allows the demonstration of the complete process chain from wood to SNG in half-commercial scale.

A consortium consisting of four partners is responsible for the PDU:

CTU – Conzepte Technik Umwelt AG

- > Repotec GmbH
- > Paul Scherrer Institute
- > Technical University Vienna

The project BioSNG is co-funded by

- the European Commission
- 6th Framework Programme PrNo TREN/05/FP6EN/ S07.56632/019895
- Swiss electric research
- Bundesförderung Österreich
- WIBAG





#### Results

- December 2008: First conversion of product gas into rawSNG
- June 2009: BioSNG at H-Gas quality produced
- June 24<sup>th</sup>: inauguration CNG cars were fuelled using BioSNG from wood
- June 2009 CNG-car was successfully used for 1000km with BioSNG





# **Quality BioSNG**

	unit	Germany DVGW regulation G260	Austria ÖVGW regulation G31	BioSNG
Wobbe Index	[kWh/m³]	12,8-15,7	13,3-15,7	14,15
Relative density	[-]	0,55-0,75	0,55-0,65	0,56
Higher heating value	[kWh/m³]	8,4-13,1	10,7-12,8	10,7




# Synthetic biofuels (FT- Route)



Cellulose, Polyose (Hemicellulose )
Lignin



i/n- paraffins (hydrocarbons)






OMV

#### Comparison of produced FT Fuels

FT- Diesel HPFT- Diesel CEC- Prüf. ACN: >72  $t_d = 2.5$  s 68.5  $t_d = 2.91$  s >51.8 / CFPP/CP/FP: -12/ -9/ - °C -62/ -60 / -98°C -18/ -5 °C




**Carbon-number** 





### Results on engine tests with 20% blends





#### Mixed alcohols

- Funded by "Klima und Energiefonds" and Bioenergy 2020+
- Aim is to get fundamental know how in the synthesis of mixed alcohols from biomass
- Main advantage is very simple gas cleaning, due to sulphur resistant catalyst

bioenergy2020+



Actual status: first experiments are done



Reformer

Drying (glycol-scrubber)

Compressor (5-7 Nm<sup>3</sup>/h; 90-300 bar)

Reactor





#### BioH2-4Refineries


Economic evaluation of production of hydrogen for a refinery

- Coordination by OMV
- ■50 MW fuel plant to replace fossil hydrogen
- Evaluation of the biomass resources available for such a plant
- Basic engineering of the gasifier as well as of all other sub units, including pipelines, utility systems, logistic needs
- Optimal use of by-products
- Economic evaluation





### Simplified flow chart





### Summary

- Biomass CHP Güssing has excellent frame conditions for R&D on synthesis gas applications
- Focus of R&D is on small CHP and on synthesis gas applications (BioSNG, Fischer Tropsch, Mixed Alcohols, Hydrogen)
- Gasification enables the conversion of biomass to many useful products

More info at http://www.ficfb.at